

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



INTERNATIONAL BUREAU OF  
INTELLECTUAL PROPERTY  
3, rue de la Harpe  
CH-1000 Nyon  
Suisse

(43) International Publication Date  
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number  
WO 2005/059374 A1

(51) International Patent Classification:  
12/20, 12/32, E04B 1/61, A47B 96/00

F16B 5/00,

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/AU2004/001777

(22) International Filing Date:

17 December 2004 (17.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003906961 17 December 2003 (17.12.2003) AU

(71) Applicant and


(72) Inventor: HUTCHENS, Ross, Manton [AU/AU]; Unit  
3/40 Gardiners Street, Goolwa, S.A. 5214 (AU).

(74) Agent: MADDERN; 1st Floor, 64 Hindmarsh Square,  
Adelaide, S.A. 5000 (AU).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A JOINER



(57) Abstract: A joiner for joining together panel members in edge to edge relationship, the joiner having a joining element (110) which defines a housing (112) which is adapted to engage within a cavity in one of the panel members, and another joining element (120) which at one end has a cavity engaging portion (121) adapted to engage within a cavity in the other panel member, and an elongate shaft (130) which extends away from portion (121) and which is provided with a plurality of teeth (131) spaced along the length thereof so as to form a rack portion, the two joining elements (110,120) being slideable relative to one another by drive means which includes a driven worm gear (150) in mesh with the rack portion, and a worm gear actuator (140) arranged, upon rotation thereof, to drive the driven worm gear (150) whereby rotary motion of the worm actuator (140) is translated into linear motion only of the shaft (130).

WO 2005/059374 A1